

DATASHEET

+32872

DISTRIBUTION ENCL (2x20) 40md D90 SM



Dimensions WxHxD (mm)	475x375x90
EAN	5600307033364
Rows x Modules	2x20
Application	Surface Mounted (SM)
No. Frames for DIN rail	2
Locking System	Flat plastic handle lock D90
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	3.65
Volume (m³)	0.027

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	07
GWT	850°C
Static Load	200kg/m ³
Installation Temperature	Mín: -25°C Máx: 55°C

Electrical Features

In	63A
Ue	230V/400V~
Ui	690V
Pde - 30K	42W
Frequency	50Hz

Included Accessories

Neutral Nº Busbars	3x(1x25mm ² + 9x16mm ²)
Earth Nº Busbars	3x(1x25mm ² + 9x16mm ²)
Blanking Plates	1x12md
Circuit Marking Labels	Yes

Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT

Nota:The image may not correspond to the product code shown. Please refer to the technical specifications.