Quitérios®

safetymax®



DATASHEET

+330

DISTRIBUTION ENCL (2x8) 16md D125 FM

Dimensions WxHxD (mm)	250x375x125
EAN	5600307030141
Rows x Modules	2x8
Application	Flush Mounted (FM)
No. Frames for DIN rail	2
Locking System	1 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	2.35
Volume (m³)	0.019

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	07
GWT	850°C
Static Load	200kg/m³
Installation Temperature	Mín: -5ºC Máx: 40ºC

Electrical Features

In	63A
Ue	230V/400V~
Ui	690V
Pde – 30K	22W
Frequency	50Hz

Included Accessories

Neutral Nº Busbars	1x(1x25mm² + 9x16mm²)
Earth Nº Busbars	1x(1x25mm² + 9x16mm²)
Blanking Plates	0,5x12md
Circuit Marking Labels	Yes

Standardizing Documentation

Standards	EN 62208
Directive	2014/35/UE
Regulations	RTIEBT

Document subject to change without previous notice

Nota: The image may not correspond to the product code shown. Please refer to the technical specifications.