

## DATASHEET

+371

### DISTRIBUTION ENCL (3x24) 72md D125 SM



<b>Dimensions WxHxD (mm)</b>	550x500x125
<b>EAN</b>	5600307030325
<b>Rows x Modules</b>	3x24
<b>Application</b>	Surface Mounted (SM)
<b>No. Frames for DIN rail</b>	3
<b>Locking System</b>	1 Curved cam plastic handle lock
<b>Color</b>	White - RAL 9010
<b>Tariff Code</b>	85381000
<b>Gross Weight (Kg)</b>	5.65
<b>Volume (m<sup>3</sup>)</b>	0.049

### Materials

<b>Enclosure</b>	Plastic - PSHI
<b>Frame and door</b>	White lacquered aluminium
<b>Chassis</b>	Aluminium
<b>BUSBARS</b>	PA support and brass busbar

### Protection and Security

<b>Insulation Class</b>	Class II Insulation
<b>IP Protection Degree</b>	54
<b>IK Protection Degree</b>	07
<b>GWT</b>	850°C
<b>Static Load</b>	200kg/m <sup>3</sup>
<b>Installation Temperature</b>	Mín: -5°C Máx: 40°C

### Electrical Features

<b>In</b>	63A
<b>Ue</b>	230V/400V~
<b>Ui</b>	690V
<b>Pde - 30K</b>	66W
<b>Frequency</b>	50Hz

### Included Accessories

<b>Neutral Nº Busbars</b>	3x(1x25mm <sup>2</sup> + 9x16mm <sup>2</sup> ) 1x(12x10mm <sup>2</sup> + 11x16mm <sup>2</sup> )
<b>Earth Nº Busbars</b>	1x(1x25mm <sup>2</sup> + 9x16mm <sup>2</sup> ) 2x(12x10mm <sup>2</sup> + 11x16mm <sup>2</sup> )
<b>Blanking Plates</b>	2x12md
<b>Circuit Marking Labels</b>	Yes

### Standardizing Documentation

<b>Standards</b>	EN 62208
------------------	----------

**Nota:**The image may not correspond to the product code shown. Please refer to the technical specifications.