

DATASHEET

+42470



DISTRIBUTION ENCL PRO (5x24) 120md D125 FM

Dimensions WxHxD (mm)	550x1000x125
EAN	5600307039793
Rows x Modules	5x24
Application	Flush Mounted (FM)
No. Frames for DIN rail	5
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	14.2
Volume (m³)	0.093

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar
Mounting Plate	Chapa zincor lacada a branco

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	09
GWT	850°C
Static Load	200kg/m ³
Installation Temperature	Mín: -5°C Máx: 40°C

Electrical Features

In	250A
Ue	230V/400V~
Ui	500V
Pde - 30K	89W
Frequency	50Hz

Included Accessories

Neutral Nº Busbars	3x(1x25mm ² + 9x16mm ²) 3x(12x10mm ² + 11x16mm ²)
Earth Nº Busbars	1x(1x25mm ² + 9x16mm ²) 4x(12x10mm ² + 11x16mm ²)
Blanking Plates	2x12md
Circuit Marking Labels	Yes
Kit Document Holder	Sim
Kit Plastic Label Holder	Sim

Standardizing Documentation

Standards

EN 62208 | EN 61439-3

Directive

2014/35/UE

Regulations

RTIEBT

Nota:The image may not correspond to the product code shown. Please refer to the technical specifications.