

**DATASHEET**

**+47206**

**GROUND MAIN TERMINAL BOX 3 IN + 5 OUT SM**



<b>Dimensions WxHxD (mm)</b>	375x250x125
<b>EAN</b>	5600307039021
<b>Application</b>	Surface Mounted (SM)
<b>Locking System</b>	Triangular plastic cam lock + key
<b>Color</b>	White - RAL 9010
<b>Tariff Code</b>	85371099
<b>Gross Weight (Kg)</b>	3.4
<b>Volume (m³)</b>	0.019
<b>Observations</b>	Equipped with a 25x6 copper bar, with removable connector, 3 inputs and 5 outputs.

**Materials**

<b>Enclosure</b>	Plastic - PSHI
<b>Frame and door</b>	White lacquered aluminium

**Protection and Security**

<b>Insulation Class</b>	Class II Insulation
<b>IP Protection Degree</b>	54
<b>IK Protection Degree</b>	07
<b>GWT</b>	850°C
<b>Static Load</b>	200kg/m3
<b>Installation Temperature</b>	Mín: -25°C Máx: 55°C

**Electrical Features**

<b>Ue</b>	230V/400V~
<b>Ui</b>	690V
<b>Frequency</b>	50Hz

**Standardizing Documentation**

<b>Standards</b>	EN 60670-22
<b>Directive</b>	2014/35/UE
<b>Regulations</b>	RTIEBT

**Nota:**The image may not correspond to the product code shown. Please refer to the technical specifications.