

DATASHEET

+42562



DISTRIBUTION ENCL PRO (5x20) 100md D200 SM

Dimensions WxHxD (mm)	475x1000x200
EAN	5600307039861
Rows x Modules	5x20
Application	Surface Mounted (SM)
No. Frames for DIN rail	5
Locking System	2 Flat plastic handle lock
Color	White - RAL 9010
Tariff Code	85381000
Gross Weight (Kg)	16
Volume (m³)	0.116

Observations Box with pre-cut slots on the top and bottom for the fixation of cable pass-through plates.

Materials

Enclosure	Plastic - PSHI
Frame and door	White lacquered aluminium
Chassis	Aluminium
BUSBARS	PA support and brass busbar
Mounting Plate	Chapa zincor lacada a branco

Protection and Security

Insulation Class	Class II Insulation
IP Protection Degree	54
IK Protection Degree	09
GWT	850°C
Static Load	200kg/m ³
Mechanical Reinforcement	Sim
Installation Temperature	Mín: -5°C Máx: 40°C

Electrical Features

In	250A
Ue	230V/400V~
Ui	500V
Pde - 30K	128W
Frequency	50Hz

Included Accessories

Neutral	3x(1x25mm ² + 9x16mm ²)
Nº Busbars	2x(12x10mm ² + 11x16mm ²)

Earth	1x(1x25mm ² + 9x16mm ²)
Nº Busbars	3x(12x10mm ² + 11x16mm ²)
Blanking Plates	2x12md
Circuit Marking Labels	Yes
Kit Document Holder	Sim
Kit Plastic Label Holder	Sim
Fixing Kit	Sim

Standardizing Documentation

Standards	EN 62208 EN 61439-3
Directive	2014/35/UE
Regulations	RTIEBT

Nota:The image may not correspond to the product code shown. Please refer to the technical specifications.